



General Product Specifications

Eureka **Stockade Inbuilt SRS5** &
Jindara **Barossa Inbuilt SRS3**

Dimensions and Specifications	
Overall Dimension (Height)	758 mm
Overall Dimension (Width)	922 mm
Fascia Depth	42 mm
Rear Casing Dimension (Height)	635 mm
Rear Casing Dimension (Width)	631 mm
Rear Casing Dimension (Depth)	430 mm
Firebox Dimension (Height)	343 mm
Firebox Dimension (Width)	500 mm
Firebox Dimension (Depth)	347 mm
Door Opening Dimension (Height x Width)	240 x 550mm
Glass Viewing Size (Height x Width)	263 x 516mm
Flue Size	150mm
Back of Fascia to Flue Centre	296 mm
Shipping weight	144kg
Linings	Firebricks on walls
Baffle thickness	8mm
Glass Type	Flat, toughened 5mm ceramic
Hearth & Clearance Requirements	
Min. Hearth Width	950 mm
Min. Hearth Depth (in front of unit)	510 mm
Min. Hearth Thickness	12 mm
Clearance to Mantle Upright	50 mm
Clearance to Mantel Shelf (from appliance base)	1390 mm
Clearance to Mantel Breast Plate (from appliance base)	1340 mm
Emissions and Efficiency	
Emissions	1.5g/kg
Efficiency	67%*
Peak Output	17kw
	*Peak efficiency % quoted
<p>CLEARANCES AND SPECIFICATIONS PROVIDED IN THIS TABLE ARE FOR REFERENCE ONLY. ALWAYS REFER TO THE OWNER'S MANUAL FOR EXACT SPECIFICATIONS PRIOR TO INSTALLATION</p>	